

ISO 9650-1

Designed for extended offshore cruising and racing, built and tested to the new comprehensive and technical ISO standard. The New ISO standard for liferafts dictate the type of materials allowed for construction and the performance requirements that have to be met covering inflation, launching, material resistance, buoyancy and interior space.

The Seago ISO 9650-1 liferaft has a large opening with an inflatable boarding step at the front of the raft with a webbing ladder inside the liferaft to allow a person wearing foul weather clothing and an inflated lifejacket to board the raft alone. The 4 water pockets underneath the raft hold a minimum of 220 Litres which guarantee complete security even in uneven loading conditions. On the underside of the raft there is a self righting stop should the liferaft inflate upside down. Also the underside of the raft is orange so it can be seen better in dark conditions should it be upside down on inflation. The Seago ISO raft is fitted with SOLAS approved reflective tape and a SOLAS approved external light.



VALISE



CONTAINER



ISO SAFETY PACK:-

- 1 X RESCUE QUOIT WITH 30M OF LINE
- 1 X PAIR OF OARS
- 2 X SPONGES
- 1 X BAILER
- 1 X WATERPROOF TORCH AND BATTERIES
- 1 X LIFE SAVING SIGNAL CARD
- 3 X RED HAND FLARES
- 1 X FLOATING KNIFE
- 1 X DROGUE (SEA ANCHOR)
- 1 X REPAIR KIT
- 6 X ANTI SEA SICKNESS TABLETS
- 1 X HAND PUMP
- 1 X WHISTLE
- 1 X WET NOTES
- 1 X SIGNAL MIRROR
- 2 X PARACHUTE ROCKETS



	Tube Dia.	Weight		Packed Dims (mm)	
		Valise	Container	Valise	Container
4 Man	2 x 215mm	34Kg	45Kg	L600 x W280 x H400	L730 x W490 x H310
6 Man	2 x 250mm	39Kg	49Kg	L700 x W270 x H400	L730 x W490 x H310
8 Man	2 x 268mm	44Kg	55Kg	L700 x W290 x H400	L780 x W530 x H365